

Step-by-Step Instructions

(PRINT this set of instructions to follow every time you refill your cartridge)

Dell Photo Color



Items needed: gloves, hand-drill, #6 refill station, Syringe , needle tip, Use Black Dye for Photo Black Photo cyan and Photo magenta , paper towels, review hints & tips and check list Note: Do not use the refill station lid for refilling this cartridge. Do not plug fill-hole after filling

Warning: Based on the nature of the formulation of our photo inks, and the use of our black dye-based ink to refill the photo black, our testing indicates that your prints may be slightly darker using Freelnk4Life™ inks with this cartridge

Syringe: Attach needle tip to the syringe tightly. Unscrew lid on ink bottle. Puncture silver seal with needle tip making a small hole in the center of seal. Using the correct color pull the correct amount of ink into the syringe. Rinse syringe and needle tip after every use and before using syringe with another color. Rinse syringe and needle tip with water until the water runs clear.

1.) Place cartridge in Station #6 with copper circuits facing to the left and the plastic feet inside the bottom of the station to your right. **Do not use the refill station lid for refilling this cartridge.** Peel back the label on top. Under label are three holes. These are your fill holes. Fill holes with colors using picture as shown. Some cartridges have squiggly lines leading to a small air hole. Enlarge that air hole with the thumb drill. These are your fill holes

2.) Insert the correct color ink using the syringe inside of each of the fill-holes. See picture and fill colors as shown. S-l-o-w-l-y release thru the syringe up to 6ml. of ink into each of the three fill-holes. Holding the bottle upside down it is 5 mls from the top to the

first marker line and then 3 mls each marker line. A little ink might come out of the top when full, so cover up the other holes while filling one.

3.) After refilling, remove cartridge from refill station. Place cartridge upright on folded paper towels with the printhead facing down toward the paper towel. Do not let the printhead touch the paper towel. It maybe necessary to tilt the cartridge slightly so printhead is not in contact with paper towel. Let cartridge sit for approximately 20 minutes after refilling before putting cartridge back into printer.

4.) Do not plug fill-hole. If the fill-holes are plugged, a slight vacuum is created. This can result in interrupted print or no print. If you place the Dell label or piece of tape over the top of the refilled cartridge & cover the holes, please use the drill to poke a hole through the label or tape of one hole. One of the three holes needs to remain completely open.

5.) Check the ink flow by gently pressing a dry paper towel against the printhead. You should see 3 small lines of each color. If not, gently press a warm, wet Paper towel against the printhead until each color is visible.

6.) When all 3 colors are visible on paper towel, place cartridge back into the printer and run 1-2 print tests. Or print 2 pages at this test site: <http://www.inkonline.net/support/colorinktest> Color Ink Test

For best results, leave cartridge in printer for 8 hours after refilling so the ink can saturate the entire sponge.

AccuBrite, Inc. is not affiliated with the listed printer manufacturers or their subsidiaries. The use by AccuBrite, Inc. does not imply endorsement by or association with the brand name owners. The listed manufacturers, printers and cartridges are used only for the purpose of showing the compatibility of this AccuBrite, Inc. product. All other trademarks, brand names and logos referenced in or on this product are the property of their respective owners. This material is protected by the copyright laws of the United States and other countries. It is illegal to reproduce these instructions. It may not be reproduced, distributed, or altered in any fashion by any entity (either internal or external to AccuBrite), except in accordance with applicable agreements or contracts of licensing, without the express written consent of AccuBrite, Inc.

Copyright © AccuBrite, Inc. 2003-2009. All rights reserved